

CLAIMS

1. (CANCELLED)
2. (CANCELLED)
3. (CANCELLED)
- 4 (CANCELLED)
- 5 (CANCELLED)
- 6(CANCELLED)
- 7(CANCELLED)
- 8(CANCELLED)
- 9(CANCELLED)
- 10(CANCELLED)
- 11 (CANCELLED)
- 12(CANCELLED)
- 13 (CANCELLED)
- 14 (CANCELLED)
- 15 (CANCELLED)
- 16 (CANCELLED)
- 17 (CANCELLED)
18. (PREVIOUSLY PRESENTED) A rope cleat which comprises:
a base having a flat surface;

an abutment means for gripping rope mounted on said base surface and having an
abutment surface perpendicular to said base surface;

a first spindle having one end mounted on said base surface and extending perpendicularly away from said base surface;

a first cam rotatably mounted on said first spindle;

said first cam having a first cam surface perpendicular to said base surface and convex toward said abutment surface;

said first cam operably arranged to permit positioning a rope between said first cam surface and said abutment surface and to provide that when tension is applied to said rope in one direction, said rope is seized between said first cam surface and abutment surface by said first cam rotating toward said abutment means and when tension is applied to said rope in an opposite direction, said rope is released from between said first cam surface and abutment surface permitting withdrawal of said rope;

a pedestal having one end secured to said base surface and extending perpendicularly away from said base surface;

a cover slidably engaging another end of said pedestal and operably arranged for sliding over said cam and an abutment between said retain position and said release position whereby said rope is retained between said abutment surface and said first cam surface when said cover is in a retain position and for permitting engagement and withdrawal of said

rope from between said abutment surface and said first cam surface when said cover is in a release position.

19 (cancelled)

20. (CURRENTLY AMENDED) A rope cleat which comprises:

a base having a flat base surface;

an abutment means for gripping rope mounted on said base surface and having an abutment surface perpendicular to said base surface;

a first spindle having one end mounted on said base surface and extending perpendicularly away from said base surface;

a first cam rotatably mounted on said first spindle;

said first cam having a first cam surface perpendicular to said base surface and convex toward said abutment surface;

said first cam operably arranged to permit positioning a rope between said first cam surface and said abutment surface and to provide that when tension is applied to said rope in one direction, said rope is seized between said first cam surface and abutment surface by said first cam rotating toward said abutment means and when tension is applied to said rope in an opposite direction, said rope is released from between said first cam surface and abutment surface permitting withdrawal of said rope;

a cover means is rotatably mounted on said abutment means [[:]] for retaining said rope between said abutment surface and said first cam surface when said cover means is in a retain position and for permitting engagement and withdrawal of said rope from between said abutment surface and said first cam surface when said cover means is in a release position;

said cover means is operably arranged to rotate between said retain and release positions [[:]] ;

said cover means has one end which is rotatable over space between said abutment surface and cam surface and a tail end;

a pin extending from said base surface on a side of said abutment means opposite said cam providing that, when said rope is positioned between said abutment surface and said cam surface and looped around said abutment surface between said pin and said abutment means, then when said cover means is rotated to said retain position, said tail end of said cover means extends over space between said pin and said abutment means.

21. (CANCELLED)

22. (CANCELLED)

23 (CANCELLED)

24. (CURRENTLY AMENDED) A rope cleat which comprises:

a base having a flat base surface;

an abutment means for gripping rope mounted on said base surface and having an abutment surface perpendicular to said base surface;

a first spindle having one end mounted on said base surface and extending perpendicularly away from said base surface;

a first cam rotatably mounted on said first spindle;

said first cam having a first cam surface perpendicular to said base surface and convex toward said abutment surface;

said first cam operably arranged to permit positioning a rope between said first cam surface and said abutment surface and to provide that when tension is applied to said rope in one direction, said rope is seized between said first cam surface and abutment surface by said first cam rotating toward said abutment means and when tension is applied to said rope in an opposite direction, said rope is released from between said first cam surface and abutment surface permitting withdrawal of said rope;

a cover means for retaining said rope between said abutment surface and said first cam surface when said cover means is in a retain position and for permitting engagement and withdrawal of said rope from between said abutment surface and said first cam surface when said cover means is in a release position;

a second cam mounted on another end of said spindle;

said second cam having a second cam surface perpendicular to said base surface and convex toward said abutment surface; and

said second cam surface operably arranged to permit positioning a rope between said second cam surface and said abutment surface providing that when tension is applied to said rope in one direction, said rope is seized between said second cam surface and abutment surface by said second cam rotating toward said abutment means[[:]] and when tension is applied to said rope in an opposite direction, said rope is seized by said first cam.

25. (CURRENTLY AMENDED) A rope cleat which comprises:

a base having a flat base surface;

an abutment means for gripping rope mounted on said base surface and having an abutment surface perpendicular to said base surface;

a first spindle having one end mounted on said base surface and extending perpendicularly away from said base surface[[:]] ;

a first cam rotatably mounted on said first spindle;

said first cam having a first cam surface perpendicular to said base surface and convex toward said abutment surface;

said first cam operably arranged to permit positioning a rope between said first cam surface and said first abutment surface and to provide that when tension is

applied to said rope in one direction, said rope is seized between said first cam surface and abutment surface by said first cam rotating toward said abutment means and when tension is applied to said rope in an opposite direction, said rope is released from between said first cam surface and abutment surface permitting withdrawal of said rope;

a cover means for retaining said rope between said abutment surface and said first cam surface when said cover means is in a retain position and for permitting engagement and withdrawal of said rope from between said abutment surface and said first cam surface when said cover means is in a release position;

a second cam mounted on another end of said spindle[[:]];

said second cam having a second cam surface perpendicular to said base surface and convex toward said abutment surface; and

said second cam surface operably arranged to permit positioning a rope between said second cam surface and said abutment surface providing that when tension is applied to said rope in one direction, said rope is seized between said second cam surface and abutment surface by said second cam rotating toward said abutment means [[:]] and when tension is applied to said rope in an opposite direction, said rope is seized by said first cam[[:]];

spring means having one spring end abutting said first cam and a second spring end abutting said second cam operably arranged to bias said first cam surface toward said abutment means and said second cam surface toward said abutment means;

means for manually rotating said first and second cams away from said abutment means.

26. (previously presented) The rope of cleat claim 24 wherein said abutment means comprises:

a first abutment having a first abutment surface facing said first cam surface;

a second abutment facing said second cam surface.

27. (canceled)

28. (PREVIOUSLY PRESENTED) A rope cleat comprising:

a base having a base surface;

a first rope abutment mounted on said base surface and having a first abutment surface perpendicular to said base surface;

a second rope abutment mounted on said base surface and having a second abutment surface perpendicular to said base surface;

a first spindle having one end mounted on said base surface and extending perpendicularly away from said base surface;

a first cam rotatably mounted on said first spindle;

said first cam having a first cam surface perpendicular to said base surface and convex toward said first abutment surface;

said first cam operably arranged to permit positioning a rope between said first cam surface and said first abutment surface and to provide that when tension is applied to said rope in one direction, said rope is seized between said first cam surface and first abutment surface by said first cam rotating toward said first rope abutment and when tension is applied to said rope in an opposite direction, said rope is released from tension and can be removed from said rope cleat;

a second cam rotatably mounted on said first spindle;

said second cam having a second cam surface perpendicular to said base surface and convex toward said second abutment surface;

said second cam operably arranged to permit positioning a rope between said second cam surface and said second abutment surface and to provide that when tension is applied to said rope in one direction, said rope is seized between said second cam surface and second abutment surface by said second cam rotating toward said second rope abutment and when tension is applied to said rope in an opposite direction, said rope is released from tension and can be removed from said cleat;

a second spindle having one end mounted on said base surface and extending perpendicularly away from said base surface;

said second spindle positioned to limit rotation of said first cam away from said first abutment and to limit rotation of said second cam away from said second abutment surface;

a spring positioned with one end abutting said first cam and another end abutting said second cam operably arranged to bias said first cam surface toward said first abutment surface and to bias said second cam surface toward said second abutment surface;

a first pedestal having one end secured to said base surface and extending perpendicularly away from said base surface;

a first cover slidably mounted on another end of said first pedestal and operably arranged to slide between a position where said rope is restrained from escaping from between said first abutment surface and said first cam surface by a first end of said first cover and a position where said rope is permitted to be engaged and withdrawn from between said first abutment surface and said first cam surface;

a second pedestal having one end secured to said base surface and extending perpendicularly away from said base surface;

a second cover slidably mounted on another end of said second pedestal and operably arranged to slide between a position where said rope is restrained from escaping from between said second abutment surface and said second cam surface by a first end of said second cover and a position where said rope is permitted to be engaged and withdrawn from between said second abutment surface and said second cam surface.

29. (PREVIOUSLY PRESENTED) The cleat of claim 28 wherein said first and second covers each have a second end opposite said respective first end operably arranged when said respective covers are in said position where said rope is restrained to extend over said base surface.

30. (CANCELLED)